

CERTIFIED CE SPRINKLER UNDER MOBIAK BRANDNAME

**FIRE EXTINGUISHERS
 CEILING
 DRY POWDER**

The Unique
 Ceiling Fire extinguishers
 in the Market
 with PT 26bar and
 Thickness
 2.5mm Providing
 Strongest Security



CODE 0135163

MBK15 - ACE1 - A0

1Kg | A B C 40

Automatic Ceiling Fire Extinguisher **1Kg**
 with Sprinkler Protective Cage
 (not included).
Height 25cm
Diameter 16cm

CE SPRINKLER

Cylinder Manufactured and Tested
 According to PED



CODE 0135164

MBK15 - ACE3 - A0

3Kg | A B C 40

Automatic Ceiling Fire Extinguisher **3Kg**
Height 27,6cm
Diameter 24cm

CE ASSEMBLY



CODE 0135121

MBK15 - ACE6 - A0R

6Kg | A B C 40

Automatic Ceiling Fire Extinguisher **6Kg**.
Height 40,5cm
Diameter 21,3cm

CE ASSEMBLY

**BIG DIAMETER
 (160mm) CONICAL HOOP**

CODE 0124046

MBK07 - MBK - CPCEILING

Automatic Ceiling Fire Extinguishers
 Fill - in Coupling

CODE 0141130

MBK14 - CEILING - PRESS

Pressure Switch
 for Ceiling Fire Extinguishers

CODE 0114052

KX11 - ACE - ADB

Adjustable Length Bracket suitable for multi
 height installation of Automatic Ceiling Fire
 Extinguishers. Mounting of the Automatic
 Ceiling Fire Extinguisher with bolt and nut.
 Length from 80 until 150cm.

METALLIC pressure gauge with
 testing hole

CEILING BRACKET with bolt and
 nut for quick and
 easy installation

68°C SPRINKLER CE certified with
 SAFETY VALVE and built-in
 Charging Valve and thread for
 fixing Pressure Gauge

CONICAL HOOP with aligned holes for better and
 overall discharge, direct control of the pressure
 gauge as well as easy refilling of the fire
 extinguisher

Recommended Pressure Switch
 (10Bars) is connected to the
 Sprinkler of the extinguisher



CERTIFIED CE SPRINKLER UNDER MOBIAK BRANDNAME

CODE 0135173

MBK15 - ACE12 - A0M

12Kg

A B C 40

Automatic Ceiling Fire Extinguisher **12Kg**.
Height 37cm. Diameter 30,2cm!

ASSEMBLY



**BIG DIAMETER
(160mm) CONICAL HOOP**

In Closed Rooms The Quantity Of The Extinguishing Agent Needed Is 12kg For An Area Of About 10m² And Height Of 1,5-2m From The Extinguishing Point. In Open Areas The Demanded Quantity Of The Extinguishing Agent Must Be Increased Due To Losses.



FIRE EXTINGUISHERS

CEILING DRY POWDER

The Unique Ceiling Fire extinguishers in the Market with PT 26bar and Thickness 2.5mm Providing Strongest Security

CODE 0135198

MBK15 - ACE12 - AOM - 122

12Kg

B C
20%

B C

Automatic Ceiling Fire Extinguisher **12Kg**.
Height 37cm. Diameter 30,2cm!

ASSEMBLY



CODE 0124046

MBK07 - MBK - CPCEILING

Automatic Ceiling Fire Extinguishers Fill - in Coupling



CODE 0141130

MBK14 - CEILING - PRESS

Pressure Switch for Ceiling Fire Extinguishers



CODE 0114052

KX11 - ACE - ADB

Adjustable Length Bracket suitable for multi height installation of Automatic Ceiling Fire Extinguishers. Mounting of the Automatic Ceiling Fire Extinguisher with bolt and nut. Length from 80 until 150cm.




METALLIC pressure gauge with testing hole



CEILING BRACKET with bolt and nut for quick and easy installation



68°C SPRINKLER CE certified with SAFETY VALVE and built-in Charging Valve and thread for fixing Pressure Gauge



CONICAL HOOP with aligned holes for better and overall discharge, direct control of the pressure gauge as well as easy refilling of the fire extinguisher



Recommended Pressure Switch (10Bars) is connected to the Sprinkler of the extinguisher

FIRE EXTINGUISHERS

HFC-227ea CLEAN AGENT CEILING

HFC-227ea is a Clean, Safe fire-fighting Agent that has excellent Fire Suppression Properties for use in Total Flooding Automatic Extinguishing Systems. HFC-227ea Automatic Fire Extinguisher Series is Ideal to Protect and Combat Fires in Engine Compartments for Land or Maritime Applications. This Automatic Extinguisher Series can be used for applications such as trucks, small boats, large boats, computer rooms, motor sport and engine plant rooms It can be used on class A, B and C fires and is also safe to use on live electrical fires.

One Unit must be installed per compartment to provide complete protection – the Protected Volume is specified by the Extinguishing Agent of the Extinguisher.

Optionally there is a low pressure warning switch which can be fitted to the Sprinkler Valve of the Extinguisher. The device continuously monitors the Extinguisher's Pressure and in the event of the pressure dropping below 10bar the switch to enable a signal to an Alarm Unit.

HFC-227ea shall not be used on fires involving the following materials unless they have been tested to the satisfaction of the authority having jurisdiction.

- Certain Chemicals or mixtures of Chemicals, such as Cellulose Nitrate and Gunpowder, that are capable of rapid oxidation in the absence of Air.
- Reactive Metals such as Lithium, Sodium, Potassium, Magnesium, Titanium, Zirconium, Uranium and Plutonium.
- Metal Hydrides.
- Chemicals Capable of undergoing auto-thermal decomposition, such as certain organic peroxide and hydrazine.







General Characteristics

- Ozone Friendly
- Leaves No Residue
- Mounting Bracket is Included
- Suitable for Class A, B and C fires
- Safe for Use on Electrical Fires
- CE Approved 68°C Sprinkler Valve
- Volume Coverage From 1.2m³ Up to 10m³
- Optional Pressure Switch
- 15Bar Stored Pressure (Nitrogen)



HFC-227ea
CLEAN AGENT
CEILING

-  Non - Corrosive
-  Ideal for Protection of Great Value Equipment
-  Does not Harm the Ozone
-  Safe for Places with Human Presence



*Environmentally
Responsible
Choice!*

FIRE EXTINGUISHERS

CEILING CLEAN AGENT / HFC-227ea

The Unique
 Ceiling Fire Extinguishers
 in the Market
 with PT 26bar and Thickness
 2.5mm Providing
 Strongest Security



CODE 0135424



MBK21 - HFC - 2

Automatic Ceiling **2Kg HFC-227ea**
 Fire Extinguisher

- 68°C Sprinkler
- Height 27,6cm
- Diameter 24cm



UL Certified HFC Agent



CODE 0135425



MBK21 - HFC - 4

Automatic Ceiling **4Kg HFC-227ea** Fire
 Extinguisher.

- 68°C Sprinkler
- Height 40,5cm
- Diameter 21,3cm



UL Certified HFC Agent



CODE 0135426



MBK21 - HFC - 8

Automatic Ceiling **8Kg HFC-227ea**
 Fire Extinguisher.

- 68°C Sprinkler
- Height 37cm
- Diameter 30,2cm



UL Certified HFC Agent



METALLIC pressure gauge
 with testing hole



CODE 0124046

MBK07 - MBK - CPCEILING

Automatic Ceiling Fire Extinguishers
 Fill - in Coupling



CODE 0141130

MBK14 - CEILING - PRESS

Pressure Switch
 for Ceiling Fire Extinguishers



CODE 0114052


KX11 - ACE - ADB

Adjustable Length Bracket suitable for multi height
 installation of Automatic Ceiling Fire Extinguishers.
 Mounting of the Automatic Ceiling Fire Extinguisher
 with bolt and nut. Length from 80 until 150cm.

CE SPRINKLER



CEILING BRACKET with bolt and
 nut for quick and
 easy installation



CONICAL HOOP with aligned holes for
 better and overall discharge, direct
 control of the pressure gauge as well as
 easy refilling of the fire extinguisher